

High-pressure Plunger Pump P3-10 Recycling

URACA

Robust and Reliable.

Small, but powerful — it is the ideal pump for sewer cleaning — now it can be used as a recycling pump too. This means greater availability and longer operation time for rough day-to-day operation. Compact design and high-quality material ensure reliable operation and increase the performance of your machine.

Advantages at a glance

- New elastomer-sealed mushroom valves to avoid particle jet erosion
- High resistance against corrosion
- Long service life through pump valves which can be used on both sides
- Plunger seal designed as maintenance-free, spring-pretensioned package with additional wear protection bushing
- Individually replacable stuffing boxes
- Protection from water entry into the power end due to isolated construction
- Fast and quick drainage due to lifting of the suction valve (optional)

URACA Pumpenfabrik GmbH & Co. KG
Sirchinger Str. 15
72574 Bad Urach, Germany
Phone +49 (71 25) 133-0
Fax +49 (71 25) 133-202
info@uraca.de
www.uraca.de

Certified according to

- DIN EN ISO 9001:2008 by LRQA
- VGB KTA 1401
- AD 2000 - HP 0
- Others on request

Typ	P3-10 Recycling
Pressure range	125 / 160 / 200 / 250 bar
Flow rate	163 l/min bei 125 bar 80 l/min bei 250 bar
Max. driving power	38 kW
Weight	ca. 83 kg

1 bar = 14.5038 psi, 1l = 0.26417 Gal., 1 kW = 1.3410 HP, 1mm = 0.03937 inch



„Small, but powerful“
– suitable for recycling
operations.

NEW

Recycling