

RV 8-28

Retaining device for heat exchanger cleaning

URACA



URACA Pumpenfabrik GmbH & Co. KG
 Sirchinger Straße 15
 D-72574 Bad Urach, Germany
 Phone +49 (71 25) 133-0
 Fax +49 (71 25) 133-202
 info@uraca.de
 www.uraca.de

Certified acc. to:
 ■ DIN EN ISO 9001: 2000 by LRQA
 ■ VGB KTA 1401
 ■ Gost




RV 8-28
Order no.
W6047-00A

Field of application

- Internal cleaning of pipes/ heat exchangers - especially with flexible lances/spirals.
- In 2 directions x/y, free-moving, exact positioning and fixing over the manhole. Distance: 0 - 900 mm.
- Safety device for the cleaning tool preventing unintended and dangerous exit of the tools out of the protecting pipe (piston effect!)
- Quick and easy clamping or tightening of the device to the heat exchanger flange.
- Drain for the discharge water protecting the service man.

Technical data	RV 8-28
Pressure range	depending on lance
Adaptable lance dia.	8,5 - 28 mm
Operating temperature	max. 70 °C
Working radius	475 mm
Weight	14 kg

Lance not included in scope of supply.



Adjustable device which can be fixed on the heat exchanger with or without bore holes.

Retaining device required by the German Trade Cooperative Association according to executory provision article 13, para 8 of VBG 87 and test certificate BAU 98078.

The multiple URACA programme completes the RV 8-28:

- Flexible lances.
- Rigid lances.
- Suitable rigid and rotating pipe cleaning nozzles.

